



GL-300/N

GL-300/N



Heavy duty gravity feed slicers Thanks to their new technical solutions like:

- High performance motor
- Gears in oil bath
- Built-in precision sharpener
- Turnable slice deflector for easy cleaning back of the knife
- High carbon steel (hard chromed) knives everybody can slice even large and heavy pieces without effort

Fan cooled motor. Continuous service. Gears and blade-holder flange run in their

own reduction box, plunged into an oil bath, securing a noiseless, durable and trouble-free traction force.



Modern sharpener provided with a movable pratechan which covers the whole blade even in all pasihan.



Removable prduct holder to make the cleaning easier. In this situahan the slice thickness control is posihaned to e (zero) to avoid accidents against the blade. This kind of accidents con occur if the slice thickness plate is unwittingly open .



Easy removable blade cover for the cleaning.
Fixed extemol blade guard to protect the blade during the cleaning opera-han.
Blade in hardened and chromium plated steel.



Opt. 93: the product holder with twa pushers (BC2) allows to cut at the II, ~bme hme products of different sizes and shapes and to guarantee the complete stability an the carriage.



Opt. 12-22: stainless tube 0 135 mm. and 9 1 BO mm. with pusher which is applicoble on the product holder. This allows to obtain a rapid ond a constant thickness cut of vegetables.

FURTHER OPTIONS:

- 8 - Pomoner: digital monitoring of the portions
- 12 - S/S vegetable tube (only on stundord conioge) (135 mm)
- 15 - Direct current motor 24 V.
- 17 - Stund for slicer
- 22 - S/S vegetable tube (only on stundord conioge) (180 mm)
- 56 - Receding feet
- 57 - Higt feet.
- 63 - Foadhalding tray
- 81 - Adiustable fence for stun-dard carriage (55 mm)

- 90 - Blade removal tool
- 93 - Carriage with 2 adjustable fixing grips BC2 for 6L slicers
- 97 - Teflon coating (gauge plate, blade, bladecover)
- 100 - Adjustable fence for standard carriage (20 mm)
- 107 - Teflon coated toothed blade 250 mm
- 108 - Teflon coated toothed blade 300 mm
- 112 - Slice holder

Electrical motor characteristics				
W	V	HZ	Phase N°	Service
270	230	50	1~	S1

GL-300/N Blade		
0mm	250	300
A	130	170
B	200	210
C	190	220
D	170	200
E	460	
F	330	
G	580	
H	420	
I	630	

